



Jeger Onyks is a ready-to-use decorative compound that allows you to achieve an original surface with shiny abrasions and pits.

You can do it
yourself
in one day!

It's just
2 steps

Only
2 tools



1 Apply Jeger
Primer Onyks
with a roller



Apply **Jeger Primer Onyks** with a microfiber roller to a clean, dry, dust-free and degreased wall. Wait 2 to 4 hours.

2 Apply Jeger
Onyks with a
trowel



Mix **Jeger Onyks** thoroughly. Do not dilute, the product is ready for use. Do not mix with other products. Moisten the surface on which you will apply Onyks with a sprayer. Apply with a Venetian trowel to the thickness of the grain, then smooth. Perform the work in stages. If you want to create pits, press and pull the trowel off the freshly applied compound. During the initial drying stage, gently smooth the entire surface. Leave to dry. Done!

Tip: If you want to achieve a sparkling crystal effect after the surface has dried, apply Jeger Silver or Gold Glitter Varnish according to the application instructions.

7 kg > ±6m²
14 kg > ±12m²

product
efficiency

jeger.com



Dependent on the substrate's texture and absorbency, thickness and number of layers, application method, and the applicator's experience.

Global Point, ul. Rozwoju 3, Biskupice Podgórne, 55-040 Kobierzyce

MADE IN POLAND