

PRODUCT NAME

Black bonding primer

PRODUCT DESCRIPTION

Black primer for Jeger Beton Black decorative effect. Evens out the absorbency of the substrate, strengthens and increases the adhesion of the decorative effect....

APPLICATION

Preparation of substrate in order to strengthen and increase adhesion under effect

Decorative Jeger Concrete.

SUBSTRATE PREPARATION

The substrate should be dry, clean and durable. Remove any damaged (e.g. flaking and cracked) coating of previous paints, adhesive and lime paints. Fill surface defects with a suitable filler and sand down. Clean previously painted surfaces of any impurities that may hinder paint adhesion, e.g. dust, greasy stains, rust, fungus and mould.

PRODUCT PREPARATION

- ✓ The primer should be mixed before use.
- ✓ Do not mix with other products.
- ✓ Do not dilute with water.

APPLICATION

Methods: roller

Apply the primer with a roller. Apply at +8°C to +25°C, relative humidity max. 82%, avoid draughts. Allow to dry for 4 hours. After this time the surface can be covered with a decorative effect. Wash the tools with warm water after use.

DRYING TIME

At +23°C and 50% relative humidity, the primer is dry to the touch after approx. 4 hours. Low temperatures, increased humidity and poor ventilation prolong the drying time.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 09.11.2022

TECHNICAL SPECIFICATIONS

Volatile Organic Compounds (VOCs) in the container EU Directive 2004/42	Category A/g/FW: EU limit value: VOC (cat A/g/FW) in a package of 30g/L (2010). This product contains less than 10g/l VOC.
Density 20°C [g/cm ³].	1,65± 2%
Solvent	Water

EFFICIENCY

±6m² from 1kg package. Performance depends on the structure and absorbency of the substrate, thickness and number of coats, application method and experience of the contractor

EXPIRY DATE

24 months from date of manufacture

PACKAGING

1kg,

ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in an appropriately labelled waste container in accordance with national regulations.

STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +25°C. Expiry date and batch number on the packaging.

SECURITY

Keep out of the reach of children. This product contains tetrahydro-1,3,4,6-tetrakis (hydroxymethyl) imidazo[4,5-d] midazol-2,5(1H,3H)-dione, 2-methyl-2H-isothiazol-3-one and a post-reaction mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May cause an allergic reaction. Seek medical advice if necessary. Avoid inhalation of spray or mist. Work in well-ventilated areas. Wear personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations. Limit

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 09.11.2022

VOC content (cat. A/g/FW) in 30g/L packaging (2010). This product contains less than 10g/l VOC.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 09.11.2022