

PRODUCT NAME

Loft Concrete

PRODUCT DESCRIPTION

Jeger Loft Concrete is a decorative compound that imitates the effect of concrete. It can be used on walls, worktops, bathrooms and showers.

APPLICATION

The decorative effect is intended for use on walls, floors, worktops, tiles, bathrooms and showers. Do not use on floors in areas intended for industrial use or intensive use.

SUBSTRATE PREPARATION

On a clean, dry, dust-free and degreased wall, apply **Jeger Primer** for wall **decorative compounds** with a roller (according to the instructions on the packaging) and allow to dry for about 2h. Apply **Jeger Primer Loft Concrete** to tiles, cement floors and worktops. Use **Jeger Levelling Primer on wall tiles and worktops** to even out joints and irregularities. Apply the primer according to the instructions on the packaging. Allow to dry for 4h.

PRODUCT PREPARATION

- ✓ Do not mix the product with others.
- ✓ Do not dilute with water.
- ✓ If several packs from different production batches are used, they should be mixed in a larger pack to prevent colour differences.

APPLICATION

Methods: trowel

Apply a thin, even layer of the darker colour with a trowel and smooth gently. Allow to dry for 4h. Then apply a second coat in vertical irregular strips, alternately mixing the darker and lighter colour. Make an irregular pattern. Gently level the damp surface. Allow to dry for at least 12 hrs. Apply at +8°C to +25°C, max. 82% relative humidity, avoiding draughts. Allow to dry for approx. 12 h.

Apply **Jeger Protector Loft Concrete for walls - matt** or **Jeger Protector Loft Concrete 2K** for floors, bathrooms and worktops with a roller. After painting, wash the tools with warm water.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 22.11.2022

DRYING TIME

At +23°C, 50% relative humidity, product dry after approx. 4 hours. Subsequent coats should be applied after approx. 4 hours. Low temperatures, increased humidity and poor ventilation prolong the drying time.

TECHNICAL SPECIFICATIONS

Volatile Organic Compounds (VOCs) in the container EU Directive 2004/42	Category A/L/FW: EU limit value: VOC (cat A/L/FW) in 200g/L package (2010). This product contains less than 12g/l VOC.
Number of layers	1-2
Solvent	Water

EFFICIENCY

Up to 6m²/l from a 2l pack. Practical efficiency depends on factors such as: type, absorbency and texture of the substrate, application method and colour.

EXPIRY DATE

24 months from date of manufacture

PACKAGING

2l

ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in a properly labelled waste container in accordance with national regulations.

STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +25°C. Expiry date and batch number on the packaging.

SECURITY

Keep out of the reach of children. This product contains 1,2-benzisothiazolin-3-one and a post-reaction mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May cause an allergic reaction. Seek medical advice if necessary.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 22.11.2022

Avoid inhalation of spray or mist. Work in well-ventilated areas. Wear personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations. VOC limit (Cat. A/L/FW) in package 200g/l (2010). This product contains less than 12g/l VOC.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 22.11.2022