

PRODUCT NAME

Onyx

PRODUCT DESCRIPTION

Jeger Onyks is a ready-to-use decorative compound that allows you to obtain an original surface with glossy rubbing and pitting.

APPLICATION

The effect is intended to be applied to walls indoors.

SUBSTRATE PREPARATION

The substrate should be dry, clean and durable. Remove any damaged (e.g. flaking and cracked) coating of previous paints, adhesive and lime paints. Fill surface defects with a suitable filler and sand down. Clean previously painted surfaces of any impurities inhibiting paint adhesion, e.g. dust, greasy stains, rust, fungus and mould. Apply **Jeger Primer Onyx** (according to the instructions on the packaging) in the colour of your choice. Allow to dry for approx. 4 hrs.

PRODUCT PREPARATION

- ✓ Mix the product thoroughly before use.
- ✓ Do not mix with other products.
- ✓ Do not dilute with water

APPLICATION

Methods: trowel

Apply with a trowel to the thickness of the grain. Apply the effect in small sections, spreading it in all directions, irregularly. Then smooth the surface. If you want to make pits, apply and detach the trowel from the freshly applied compound. Smooth gently over the entire surface during the initial drying stage. Apply at a temperature of +8°C to +25°C, at a relative humidity of max. 82%, avoiding draughts. Let dry for approx. 24 hours. Wash the painting tools with warm water after use.

Tips: If you want to achieve a shimmering crystal effect before applying, add Jeger **Brocade** (approx. 100g for every 7kg of product) to **Jeger Onyx** and mix thoroughly.

DRYING TIME

At +23°C and 50% relative humidity, the product is dry after 24 hours. Low temperatures, increased humidity and poor ventilation prolong the drying time.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date:27.09.2022

TECHNICAL SPECIFICATIONS

Volatile Organic Compounds (VOCs) in the container EU Directive 2004/42	Category A/L/FW: EU limit value: 200 g/l (2010) This product contains less than 1 g/l VOC
Number of layers	1
Solvent	Water

EFFICIENCY

Capacity: 7kg =±6m²; 14kg =± 12m²*.

*Effectiveness depends on the structure and absorbency of the substrate, thickness and number of coats,
the application method and the contractor's experience.

EXPIRY DATE

24 months from date of manufacture

PACKAGING

7kg, 14kg

ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in a properly labelled waste container in accordance with national regulations.

STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +25°C. Expiry date and batch number on the packaging.

SECURITY

Keep out of the reach of children. This product contains tetrahydro-1,3,4,6-tetrakis (hydroxymethyl) imidazo[4,5-d] midazol-2,5(1H,3H)-dione, 1,2-benzisothiazolin-3-one and a post-reaction mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May cause an allergic reaction. Seek medical advice if necessary. Avoid inhalation of spray or mist. Work in well-ventilated areas. Wear personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations. Limit

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date:27.09.2022

VOC content (cat. A/L/FW) of 200g/L (2010). This product contains less than 1g/l VOC.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date:27.09.2022