

PRODUCT NAME

PRIMER FOR DECORATIVE PAINTS

PRODUCT DESCRIPTION

Primer for decorative paints intended for priming walls and ceilings indoors. Reduces absorption of the substrate. Improves the final appearance of the applied decorative effect. Easy to apply.

APPLICATION

Primer interior painting of walls in residential, office and public premises, healthcare facilities and service establishments. Can be used, among other things, on plasterboard, cement-lime plaster, previously painted surfaces, wallpaper, etc.

SUBSTRATE PREPARATION

Previously painted surfaces should be cleaned of impurities that limit paint adhesion, e.g. dust, greasy stains, rust, fungus and mould. The substrate should be dry, clean and durable. Damaged (e.g. flaking and cracked) coatings of previous paints, adhesive and lime paints should be removed. Fill surface defects with a suitable filler.

Paint fresh plaster after the seasoning period (3-4 weeks after application) after prior sanding and dust removal. For very absorbent substrates, priming with Jeger Gel Primer is additionally recommended.

PRODUCT PREPARATION

- ✓ The paint should be mixed thoroughly before use.
- ✓ Do not mix the paint with other paints.
- ✓ If several packs from different production batches are used, they should be mixed in a larger pack to prevent differences in colour shades.
- ✓ If necessary, it is permissible to dilute the paint with water up to a maximum of 5%.

APPLICATION

Methods: roller, brush, spray

Apply two coats of paint to a suitably prepared substrate using Globall brand microfibre brush or roller. For very dark or contrasting colours it may be necessary to apply 3 coats of paint.

Application by spraying possible (nozzle: 0,014"-0,019", pressure:100-120bar). Apply on a solid, clean, dry substrate at a temperature of +8°C to +25^(o) C and a relative humidity of max. 82 %, avoiding draughts. Apply the paint carefully and evenly. Apply in all directions and

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 11.03.2022

make the last stroke in the same direction. Paint tapes are best removed immediately after painting.

Apply the next coat after approximately 2 hours. The paint film acquires its full strength properties 28 days after the completion of the painting work carried out in accordance with the manufacturer's instructions. Wash the painting tools with water after completion of painting.

DRYING TIME

At +23°C and 50% relative humidity, the paint is dry to the touch after approx. 1 hour. Subsequent coats should be applied after approx. 2 hours. Low temperatures, increased humidity and poor ventilation prolong the drying time.

TECHNICAL SPECIFICATIONS

Volatile Organic Compounds (VOCs) in the container EU Directive 2004/42	Category II/Ag: EU limit value: 30 g/l (2010) This product contains less than 1 g/l VOC
Density 20°C [g/cm ³].	1.4± 2%
Degree of gloss PNC 81914:2002	matt
Number of layers *depending on colour	1-2
Solvent	Water
Colour	white

EFFICIENCY

Up to 16m²/L in a single coat. Practical performance depends on factors such as the type, absorbency and texture of the substrate, the application method and the colour.

EXPIRY DATE

24 months from date of manufacture

PACKAGING

1L

ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in an appropriately labelled waste container in accordance with national regulations.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 11.03.2022

STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +25^(o) °C. Expiry date and batch number on the packaging.

SECURITY

Keep out of the reach of children. This product contains 2-methylisothiazol-3(2H), 1,2-benzisothiazol-2(2H)-one and a post-reaction mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May cause an allergic reaction. Seek medical advice if necessary. Avoid inhalation of spray or mist. Work in well-ventilated areas. Wear personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations. VOC content limit (Cat. A/a/FW) per package 30g/L (2010). This product contains less than 1g/L VOC.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 11.03.2022