

PRODUCT NAME

Loft Concrete Protector for floors, bathrooms and countertops

PRODUCT DESCRIPTION

Jeger Loft Concrete Protector for floors, bathrooms and worktops creates a protective coating that is extremely scratch and impact resistant. Ideal for bathrooms, shower showers, floors and worktops. Easily washable, does not fade and permanently protects against dirt.

APPLICATION

The lacquer is intended for use as a protective layer for the Loft Concrete effect. Not for use in PVC shower enclosures.

SUBSTRATE PREPARATION

The substrate should be dry, clean and durable. Clean the surfaces of impurities that limit the adhesion of the varnish, e.g. dust, greasy stains, rust, fungus and mould.

PRODUCT PREPARATION

- ✓ The product should be mixed thoroughly before use.
- ✓ Do not mix the product with others.
- ✓ If several packs from different production batches are used, they should be mixed in a larger pack to prevent differences in gloss.
- ✓ For the application of the first coat of the product, dilute part of the product with 30% of the water.

APPLICATION

Methods: roller

Apply the first coat quickly and evenly with a roller. Apply in a criss-cross motion over an area of 1-2m², then immediately smooth out with light movements. After 4 hours, apply a second, undiluted layer in the same way. Do not apply thick layers. Apply at +8°C to +25°C, relative humidity max. 82%, avoid drafts. Allow to dry for approx. 4 h. Wash the painting tools with warm water after use.

For shower applications, apply silicone grout after the coating has dried completely (after 48 hours) in the corners of the shower enclosure and around the bottom plug opening. Allow to dry for 24 hours. The coating becomes fully usable after 15 days.

Note: In areas exposed to dirt and water, apply a third coat.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 08.05.2025

DRYING TIME

At +23°C and 50% relative humidity, the paint is dry to the touch after approx. 4 hours. Subsequent coats should be applied after approx. 4 hours. Low temperatures, increased humidity and poor ventilation prolong the drying time.

TECHNICAL SPECIFICATIONS

Volatile Organic Compounds (VOCs) in the container EU Directive 2004/42	Category A/e/FW: EU limit value: VOC (cat. A/e/FW) in package 130g/L (2010). This product contains less than 65g/l VOC.
Density 20°C [g/cm ³].	1,05± 2%
Degree of gloss PNC 81914:2002	matt
Number of layers	1-3
Solvent	Water

EFFICIENCY

Up to 8m²/L in one application. Practical performance depends on factors such as the type, absorbency and texture of the substrate, the application method.

EXPIRY DATE

24 months from date of manufacture

PACKAGING

1l

ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in a properly labelled waste container in accordance with national regulations.

STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +25^(o) °C. Expiry date and batch number on the packaging.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 08.05.2025

SECURITY

Keep out of the reach of children. Product contains Terbutryn; 1,2-benzisothiazol-3(2H)-one; 2-octyl-2H-isothiazol-3-one; post-reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May cause an allergic reaction. Seek medical advice if necessary. Avoid inhalation of spray or mist. Work in well-ventilated areas. Wear personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations. VOC content limit (Cat. A/L/FW) per package 200g/L (2010). This product contains less than 65g/l VOC. Safety data sheet, instructions and detailed product safety information available at: jeger.co.uk/info

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 08.05.2025