

PRODUCT NAME

Stucco White Collection

PRODUCT DESCRIPTION

Jeger Stiuk White collection is a white deco effect with a distinctive, elegant sheen. It gives walls a polished marble effect, adding a luxurious touch to interiors.

APPLICATION

The effect is intended to be applied to walls indoors.

SUBSTRATE PREPARATION

The substrate should be dry, clean and durable. Remove any damaged (e.g. flaking and cracked) coating of previous paints, adhesive and lime paints. Fill surface defects with a suitable filler and sand down. Clean previously painted surfaces of any impurities that hinder paint adhesion, e.g. dust, greasy stains, rust, fungus and mould. Apply Jeger Decorative Primer to the surface according to the instructions on the packaging (two are recommended for light colours). Allow to dry for approximately 2 hours.

PRODUCT PREPARATION

- ✓ Mix the product thoroughly before use.
- ✓ Do not mix with other products.
- ✓ Do not dilute with water

APPLICATION

Methods: trowel

Apply a thin layer evenly using a Venetian trowel. Apply the effect in small sections, spreading in all directions, irregularly. Allow to dry for 2h. Before applying the second coat, smooth the surface with a trowel by pressing against the wall surface. Apply the second coat in small sections, spreading the product all directions. When the material starts to dry, start the glossing by pressing with a trowel and polishing in all directions. Apply at a temperature of +8°C to +25°C, with a maximum relative humidity of 82%, avoiding draughts. Wash tools with warm water after use.

Tip: For a highly polished effect. Approximately 2 hours after applying the second coat of Stiuk, mechanically polish the entire surface with a polishing fur. For improved colour depth and high gloss, apply **Jeger Decorative Wax** for Stiuk effect and polish again.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

GLOBAL POINT Sp. z o.o. Sp. Komandytowa
3 Development Street, Biskupice Podgórne55-040
Kobierzyce
Telephone: 887 71 71 04
jeger@jeger.pl

Update date:05.12.2024

Remember: If you need to use more than one pack of product, mix the contents of all packs together before applying. This will ensure a uniform shade. Test the effect on a small area before application. The product is intended for interior use.

DRYING TIME

At +23°C, 50% relative humidity, the product is dry after 2-4 hours, apply the next coat after this time. Low temperatures, increased humidity and poor ventilation prolong the drying time.

EFFICIENCY

12 m² from a 2 litre pack.

The efficiency of the effect depends on the structure and absorbency of the substrate, the thickness of the application, the application method and the experience of the contractor .

EXPIRY DATE

24 months from date of manufacture

PACKAGING

2L

ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in a properly labelled waste container in accordance with national regulations.

STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +25°C. Expiry date and batch number on the packaging.

SECURITY

Keep out of the reach of children. This product contains 1,2-benzisothiazol-2(2H)-one and a post-reaction mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May cause an allergic reaction. Seek medical advice if necessary. Avoid inhalation of spray or mist. Work in well-ventilated areas. Wear personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations. VOC content limit (Cat. A/L/FW) per package 200g/L (2010). This product contains less than 5g/L VOC.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

GLOBAL POINT Sp. z o.o. Sp. Komandytowa
3 Development Street, Biskupice Podgórne55-040
Kobierzyce
Telephone: 887 71 71 04
jeger@jeger.pl

Update date:05.12.2024